

WL Cube Firewall™

First class purification performance in a distinct compact unit

Excellent, thoroughly purified water for small workplaces

With its sophisticated and premium look, the WL Cube Firewall (WL Cube FW) is the ideal worktop solution for small working environments, meeting rooms, kitchens, bar and break areas.

Advanced technology

The WL Cube FW features three core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's Gold Seal of approval, meaning they offer the best possible filtration.



Firewall

Waterlogic's patented Firewall technology utilises a highly effective UVC purification system at the point of dispense. Firewall guarantees 99.9999% purified water. Glass after glass.



BioCote® protection

The WL Cube FW key surfaces are infused with BioCote, a silver ion additive able to inhibit microbial growth on the surface of the products helping to reduce unpleasant odours, degradation of key surfaces and the potential for cross contamination.



Standard model

Expert purification

Featuring Firewall, which thoroughly purifies the water as it is dispensed, acting also as a barrier preventing back contamination from outside, the WL Cube FW is the only compact machine on the market delivering totally safe cold, ambient and sparkling water, cleansed from pathogens by up to 99.9999%.

Features

Firewall, patented UV technology reduces the risks of bacteria, viruses, and cysts purifying the water up to 99.9999%, 100% of the time

Removable drip tray to easily accommodate average size sport bottles








Elegant touch sensitive control panel for ease of use

Energy saving sleep mode to reduce power consumption when unit is not in use

LED UV fault indicator for easier servicing and peace of mind

BioCote® protected dispensing area

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					

Technical specifications

Types available

Countertop

Dimensions

Standard model

Cube: 296mm/11.6" (W) x 375mm/14.8" (H) x 425mm/16.7" (D)

Sparkling model

296mm/11.6" (W) x 376mm/14.8" (H) x 527mm/20.8" (D)

Dispensing area height

155mm/6.10" (with drip tray)

247mm/9.7" (without drip tray)

Weight

Standard model: 18 KG/ ~39 lbs

Sparkling model: 19 KG/ ~42 lbs

Standard filtration supplied

Carbon

Storage capacity

Standard model:

Cold tank 1.4 litre. Hot tank 1.3 litre

Sparkling model:

Cold tank 1.3 litre. Sparkling tank 0.5 litre

Water temperatures settings

Cold 5-15°C / 41-59°F

Hot 87-95°C / 188.6-203°F

Number of users

 1-7



Sparkling model

Tested and certified

NSF/ANSI-55 Class A
Ultra-violet Microbiological
Water Treatment Systems
NSF P231
Protocol for
Microbiological Purifiers



CE QUALITY & SAFETY
GUARANTEED

*certificate may vary depending on different models or products

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Contact the export team today

Waterlogic Trading Ltd

+ 353 1 293 1960

exportsales@waterlogic.com

For more information, visit www.waterlogic.com