

# WL H1 Bar - Series E

A high capacity, elegant and compact unit for the HORECA sector



Electronic model



*\*R290 gas available on 230v models only*

## Designed with the hospitality sector in mind

WL H1 Bar - Series E efficiently addresses high volume for cold, ambient and sparkling water even at peak times, for fast bottle and carafe filling. A unique and smart design for a features-rich worktop dispenser.

## Leading technology

The WL H1 Bar - Series E features two core technologies:



### Ice Bank cooling system

The Ice Bank cooling technology is paramount to the HORECA needs, where large quantities of consistently ice-cold water are required.



### Performance filtration

Professional grade filters are used to satisfy the need for high water consumption, addressing colour, taste and odour, for great tasting, crystal-clear water.

## Professional water dispensing for commercial environments

WL H1 Bar - Series E is the recommended solution for catering and intensive use environments such as bars, restaurants, cafeterias, conference centers.

## Features

- Clean design and external surfaces in stainless steel
- Adjustable drip tray height to easily fill different sized bottles and carafes
- Three water dispensing options, cold, ambient and sparkling, with professional grade carbonator in stainless steel
- Practical taps allow three bottles to be filled at the same time
- Electronic model features portion control function to preset the volume of water dispensed
- Eco-sustainable refrigeration using R290 natural gas, for low environmental impact
- Energy saving, standby function reduces overall power consumption by 75% compared to full operation mode (available on electronic models only)
- Optional UVC light (available on electronic models only)



Tap model

Model	Tap	Electronic	Tap	Electronic
<b>Dispensing capacity</b>	80 L/h		150 L/h	
<b>Water options</b>				
<b>Dispensing operation</b>	Manual mechanical taps	Push buttons	Manual mechanical taps	Push buttons
<b>Weight</b>	35 kg		46 kg	
<b>Dimensions</b>	345 mm 592 mm 580 mm	345 mm 592 mm 555 mm	488 mm 589 mm 580 mm	488 mm 589 mm 555 mm
<b>Dispensing area</b>	203-242 mm 280-332 mm	238-277 mm 315-372 mm	202-240 mm 279-336 mm	237-275 mm 314-370 mm
<b>Portion control</b>	n/a	Yes	n/a	Yes
<b>Energy saving</b>	n/a	Yes	n/a	Yes
<b>Compressor</b>	(R290 gas) 230v - 50Hz (1/5 HP) (R134a gas) 115v - 60Hz (360 kcal/h)		(R290 gas) 230v - 50Hz (1/5 HP) (R134a gas) 115v - 60Hz (360 kcal/h)	
<b>Water temperature</b>	5°-12°C/41°- 54°F		5°-12°C/41°- 54°F	
<b>UVC</b>	n/a	Yes	n/a	Yes

## Tested and certified



Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice.

## Contact the export team today

**Waterlogic Trading Ltd**  
+ 353 1 293 1960  
exportsales@waterlogic.com

For more information, visit [www.waterlogic.com](http://www.waterlogic.com)