

WL100

Convenient water dispensing unit for budget applications



R600a gas

**Zero
environmental
impact**



Economical POU solution for perfectly chilled and hot water

A great value dispenser supplying safe and refreshing drinking water for the workplace without the hassle of bottles. Recommended for up to 20 users, WL100 is the ideal solution for basic hydration needs at a competitive price.

Advanced technology

The WL100 features two core technologies:



High performance filtration

Waterlogic's filters are certified to stringent standards, carrying the Water Quality Association's Gold Seal of approval, meaning they offer the best possible filtration. This guarantees each drop is as good as the last.



BioCote® protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote®, a silver ion additive that provides continuous antimicrobial protection against a broad spectrum of bacteria, mould and fungi, and reduces the risk of cross-contamination.

Waterlogic's promise

Waterlogic combines water science and the latest technologies available to offer safe, great tasting water, whilst preserving the health integrity of the workplace.

Features

Ergonomic design with simple buttons and icons for easy dispensing operation





Environmentally friendly refrigeration with R600a: natural occurring refrigerating gas with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)

Generous drip tray capacity to collect accidental spillage

BioCote® protected dispensing area (including drip tray body, cold faucet and dispensing buttons)

Easy connection to the existing mains water supply

Water options

	cold	sparkling	ambient	hot	extra hot
1					
2					

Number of users

 10 - 20

Tested and certified



CE QUALITY & SAFETY
GUARANTEED

Waterlogic International Limited and WLI Trading Limited reserve the right, in order to reflect continuous research and development, to amend or change specifications without prior notice. Waterlogic and the Waterlogic logo, Firewall and the Firewall logo are trademarks in countries where the Group operates. WLI Trading Ltd licensed to use BioCote, and BioCote logo which are registered trademarks of BioCote Ltd.

Technical specifications

Types available

Freestanding and countertop

Dimensions

Freestanding:

345mm/13.6" (W) x 1030mm/40.6" (H) x 367mm/14.4" (D)

Countertop:

345mm/13.6" (W) x 457mm/18" (H) x 367mm/14.4" (D)

Dispense area height

220 mm/8.7"

Weight (Hot and cold models)

Freestanding: 28 kg/~61.7 lbs

Countertop: 23 kg/~50.7 lbs

Standard filtration supplied

Carbon

Storage capacity

Cold tank: 2 litres (~0.44 US gal.)

Hot tank: 1.5 litres (0.4 US gal.)

Drip tray capacity

1.5 litres

Compressor

220/240v 50Hz (R600a)

Water temperatures settings

Cold: 5-8°C/41-46.4°F (default set at 5°C/41°F)

Hot: 85-90°C/185-194°F



Contact the export team today

Waterlogic Trading Ltd

+ 353 1 293 1960

exportsales@waterlogic.com

For more information, visit www.waterlogic.com